

805 Pop-up

Impact Sprinkler

Primary applications: Residential and public lawns

Main features

- Reliable impact plastic head for underground installation
- Full- or part-circle pattern adjustment.
- Diffuser screw breaks water into smaller droplets for uniform watering
- Extra high 7.60 cm pop-up clearance
- Rugged ribbing case for maximum strength and durability, also provides anti-vandalism anchorage
- Sand-proof seals and removable filter screen for easy maintenance
- Colour-coded nozzles

Technical data

Spacing between sprinklers: up to 12.0 m

Pressure: 2.0 - 4.0 bar

1/2" Female water inlet



Performance table

| Nozzle mm | P bar | Q m ³ /h | D m |
|--------------|----------|------------------------|--------|
| 2.8 | 2.0 | 0.45 | 21 |
| Orange | 3.0 | 0.55 | 23 |
| | 4.0 | 0.63 | 23 |
| 3.0 | 2.0 | 0.51 | 22 |
| Red | 3.0 | 0.63 | 24 |
| | 4.0 | 0.72 | 25 |
| 3.2 | 2.0 | 0.57 | 23 |
| Green | 3.0 | 0.70 | 24 |
| | 4.0 | 0.81 | 25 |
| 3.5 | 2.0 | 0.66 | 23 |
| Blue | 3.0 | 0.81 | 24 |
| | 4.0 | 0.93 | 26 |
| 4.0* | 2.0 | 0.85 | 24 |
| Black | 3.0 | 1.03 | 25 |
| | 4.0 | 1.18 | 26 |

* Standard nozzle